

CLAIMS

1. A child car seat capable of being mounted on a stroller body including a front leg, a hand push rod, and an armrest, comprising;
 - a child car seat body to be fitted in the stroller body;
 - a locking member disposed on the child car seat body to be engaged with the armrest of the stroller body;
 - a locking/unlocking mechanism disposed on the locking member for locking the child car seat on the stroller body, and having a locking/unlocking lever, the locking/unlocking mechanism being unlocked and maintained in the unlocked state upon an operation of the locking/unlocking lever; and
 - a fall prevention member which contacts the stroller body for preventing the child car seat from falling off the stroller body.
2. The child car seat according to claim 1, wherein the fall prevention member extends downwardly from the locking member to contact the front leg of the stroller body.
3. The child car seat according to claim 1, wherein the fall prevention member includes a laterally extended locking rod which is mounted on a lower end of a lever extending downwardly from the locking member.
4. The child car seat according to claim 3, wherein the locking rod contacts the front leg of the stroller body.
5. The child car seat according to claim 1, wherein the fall prevention member includes a pair of levers extending downwardly from the locking member with sandwiching therebetween an armrest boss part projected from a front end of the armrest, and a locking rod connecting lower ends of the pair of levers and positioned forward the front leg.
6. The child car seat according to claim 1, wherein the fall prevention member includes an inclination prevention

plate disposed on the locking member to be engaged with a boss laterally projected from the front leg of the stroller body.

7. The child car seat according to claim 6, wherein the inclination prevention plate has a recess to be engaged with the boss.

8. The child car seat according to claim 7, wherein the inclination prevention plate has a slit adjacent to the recess to extend in an advancing direction of the stroller body.

9. The car seat according to claim 1, wherein the fall prevention member includes a locking lever projected from the locking member and extending rearward the stroller body to contact a boss projected from the hand push rod of the stroller body.

10. The child car seat according to claim 9, wherein the locking lever is upwardly swingable, and is urged to project rearward the stroller body.

11. The car child seat according to claim 10, wherein a spring is disposed between the locking lever and the locking member.